



T5 Lights (0.5ft / 1ft / 2ft/ 3ft / 4ft)

Eliteline

01 Lighting Parameters



ProductName	T5 Light
Model:	EL-T5-0.5FT/1FT/2FT/3FT/4FT-3CCT
Driver:	AdjustableCCT
Power:	3W/5W/9W/13W/18W
Voltage:	120V/50/60HZ
ProductSize:	0.5FT / 1FT / 2FT / 3FT / 4FT
CRI	Ra>80
CCT:	3000K/4000K/5000K
Beam Angle:	130°
Cover Type	Frosted Finish
Color:	White
Lumen:	250 lm / 500lm / 900lm / 1300lm / 1800lm

02 Features


- Using high-brightness LED chip, energy saving and environmental protection, stable lighting, long service life
- Frosted finish optical grade lampshade, good light, anti-aging, not easy to damage
- Linkable up to 16pcs. with integrated driver
- 3CCT Adjustable colour temperature
- Used for an extensive range of surface mounting applications.
- Available in different sizes including 0.5ft, 1ft, 2ft, 3ft, and 4ft.

03 CCT Instructions



EL-T5-0.5FT/1FT/2FT/3FT/4FT-3CCT

- T5 light in 3000K/4000K/5000K
- T5 luminaire DEL 3000K/4000K/5000K



There is a dip switch on the light fixture that marks 3000K/4000K/5000K. The dip switch is also called CCT selectable.

By dip switch

Select certain color temperature (3000K/4000K/5000K) on dip switch, then the light will be that color.

HARDWARE CONTENTS

- x2 Mounting Screws (4x22mm)
- x2 Mounting Screws (4x16mm)
- x2 Clips
- x2 Roll plug
- female end cap

See reverse side for more information
Voir au verso pour plus d'information



04 Colour



● 3000K

● 4000K

● 5000K

05 Accessories




Power Cord



connecting cable
(Sell Separately)



1.2M power cord with plug on
one end and another male end
(Sell Separately)



wire box with female end & on/off switch
(Sell Separately)

06 Installation

1. Drill two holes at the desired location on the wall (the holes should be near the two ends of the T5 fixture). Then put the roll plugs in the holes.
2. Select suitable size of screws and then put the clip on the screw, then screw in both screws and clips into the roll plug.
3. Use the switch on the T5 fixture to choose a color temperature before installing.
4. Make sure the clips are installed in place tightly. Then click the T5 fixture in the clips.
5. Linking options
 - For 3ft (900mm) T5 fixture, you can link 6 pcs at maximum.
 - For 4ft (1200mm) T5 fixture, you can link 3 pcs at maximum.
6. If the T5 fixtures are installed on different horizontal line.
 - You can use the connecting cable to connect the two T5 fixtures.
 - Make sure everything is connected properly.
 - Put the female end cap at the end of last T5 fixture.
 - Connect the power cord with the male end of first T5 fixture.
 - Then connect with the power.

